

Automatic Strapping Machine

- **Strapping Speed**
Standard strapping rate is 31 straps/min.
- **Jam Resistant**
The iQ-4000 automatically re-feeds the strap when a misfeed occurs. The strap will not jam if the machine is cycled with no package under the arch.
- **Strapping sizes:**
The iQ-4000 can be easily adjusted for strap widths of 3/8" and 1/2".



iQ-4000

Weight	100 kg	220 lbs.
Joint / Strap	heat seal / polypropylene	heat seal / polypropylene
Strap	(5, 6)**, 9, 12, 15.5 mm	(1/4)**, 3/8, 1/2 in.
Strap Tension	392 N (40 kgf)	88 lbf
Power Supply	110, 120, 220, 230, 240V Single phase	

**Narrow width parts are not available this time
Dimensions and specifications are subject to change without notice.

Modification rights reserved.

ISO 9001 and 14001 Certified

© 2024 Strapack Corporation

DISTRIBUTED BY:

PACKSOURCE

(800) 464-3100

Systems

Innovation in Packaging Supplies • Machinery • Service • Design

Packsource Systems, Inc.

2158 Union Place, Simi Valley, CA. 93065
Phone 1-800-464-3100 Fax. 1-805-520-7555

Mike Ferrato- Strapping Specialist

mike@packsourcesys.com
www.packsourcesys.com